



## Hanover Foils Success Story



### The Challenge: Wrinkling Issues

Hanover Foils, LLC, a flexible packaging converting company located in Ashland, VA, specializes in coated foil and film and foil laminations for a variety of industries including food and beverage and medical, pharmaceutical, and nutraceutical. They run several process lines in their 80,000 sq/ft facility including rotogravure printing/coating, laminating, specialty rewinding, and coil slitting.

When they began having severe wrinkling issues in one of their spooling/embossing lines, as well as continuous tracking issues in their two-unit coater line, they were referred to OASIS Alignment Services for help.

### OASIS Troubleshoots Lines

Hanover Foils initially hired OASIS to inspect the spooler/embosser because they were experiencing an excessive amount of waste due to wrinkling when running thin gauge foil. The spooler/embosser is approximately 20' long and 6' wide and contains 12 rolls. Using optical alignment tooling, the OASIS team inspected the embosser unit and unwind stand for parallelism to the rewind.

The survey showed that there was severe misalignment between the embosser, rewind and unwind stand. This information was discussed with the Hanover Foil team and it was determined that a complete alignment should be performed. An alignment tolerance of 0.003" was established and all rolls within the line were then set to this tolerance. Since the realignment, this line runs with little to no waste due to wrinkling.

Because of the positive results generated on the spooler/embosser, Hanover Foils asked OASIS to inspect their two-unit coater line. This line consists of two coater units and ovens and is made up of 60 rolls.

The line had been experiencing product tracking issues in the first coater oven for a long period of time. So much so, that the first coater unit and oven could not be used. In order to run the line, a roll was added to the machine to bypass the first coater oven. They were able to run quality product, but were running the product through the process twice. In addition to the time it took to run the process, the energy consumption from this one line was exorbitant.

***“Thank you to the  
OASIS team for a  
job well done!”***

An OASIS team was hired to inspect and align the line to a tolerance of 0.005". Again using optical alignment tooling, OASIS engineers inspected the entire line and performed the realignment. The team at Hanover Foils were so pleased with the results, Howard Hager, President of Hanover Foils, sent the following:

***“We have been up and running for a full day now – the work that OASIS performed has helped tremendously. This is the first time we have ever been able to run the full machine without issue. Thank you to the OASIS team for a job well done!”***



For more information on how the precision alignment of YOUR coating/laminating equipment can help to improve operating efficiency and reduce waste, please [contact us](#) for a site visit. Be sure to [subscribe](#) to our blog for industry news, technology updates and more!